VarioCAM[®] HDx head

Entry-level Access to Stationary Thermography at Premium Level





Europe's leading specialist for infrared sensors and measurement technology

Microbolometer detector with (640 × 480) IR pixels GigE Vision interface Robust light metal housing (IP67) Wide range of lenses Convenient camera control and data acquisition Made in Germany





VarioCAM® HDx head
Optimisation of electronic components
Heating of a drive



www.InfraTec.eu

termovize "TMV SS" spol. s.r.o. obchodní s servisní zastoupení pro ČR a SR

Studánková 395, 149 00 Praha 4 - Újezd tel.: +420 272 942 720, fax: +420 272 942 722 email: info@tmvss.cz, www.tmvss.cz



Spectral range	(7.5 14) μm	
Detector	Uncooled microbolometer focal-plane array	
Detector format (IR pixels)	(640×480)	
Temperature measuring range	(-40 600) °C, optional up to 1,200 °C*	
Measurement accuracy	± 2 °C or ± 2%	
Temperature resolution @ 30 °C	Up to 0.03 K*	
Frame rate	Full-frame: 30 Hz (640 × 480), sub-frame: 60 Hz (384 × 288)	
Window mode*	Yes	
Storage media	SDHC Card, external control computer for camera control and data acquisition*	
Image storage	Time-, trigger- and temperature controlled recording of 16 bit single frames or image sequences with	
	timestamp, video streaming in MPEG format	
Lens mount	Automatic objective detection	
Focus	Motor-driven, automatic or manual, accurately adjustable	
Zoom	Up to 32× digital, stepless	
Dynamic range	16 bit	
Personnel detection range	Up to 2.0 km with VarioCAM® HDx head security/40 mm lens	
Vehicle detection range	Up to 4.2 km with VarioCAM® HDx head security/40 mm lens	
Interfaces	GigE Vision, DVI-D (HDMI), C-Video, RS232, WLAN*, Process interface*	
Trigger*	2 × digital I/O, 2 × analogue I/O	
Tripod adapter	1/4" photo thread	
Power supply	AC adapter, (12 24) V DC, PoE*	
Storage and operation temperature	(-40 70) °C, (-25 55) °C	
Protection degree	IP54, IEC 60529, IP67 with screw-on interface*	
Impact strength, vibration resistance in operation	25 G (IEC 68 - 2 - 29), 2 G (IEC 68 - 2 - 6)	
Dimensions, weight	$(221 \times 90 \times 94)$ mm, 1.15 kg (basic configuration with standard lens)	
Further functions*	Camera internal emissivity correction, shutter free operation, temperature alarm	
Analysis and evaluation software*	IRBIS® 3, IRBIS® 3 plus, IRBIS® 3 professional, IRBIS® 3 view, IRBIS® 3 remote, IRBIS® 3 online,	
	IRBIS® 3 process, IRBIS® 3 vision, IRBIS® 3 active, IRBIS® 3 mosaic	

* Depending on model

The thermographic camera VarioCAM[®] HDx head is based on an uncooled microbolometer FPA detector with (640 × 480) IR pixels. Thanks to its wide standard temperature measuring range it is suitable for universal measuring, testing and monitoring tasks in many sectors.

Even the low-cost models of the VarioCAM® HDx head as entry-level access to the class of professional, stationary microbolometer thermography systems provide brilliant thermographic images in high quality that can be created and evaluated very easily using the powerful software family IRBIS® 3. The high-quality processing, modular design and motorised focusing are among the details that benefit users.

The VarioCAM® HDx head convinces with its **extensive range of standard options.** The range includes automatic threshold detection and signalling by means of digital real-time image acquisition via the **integrated GigE Vision interface** as well as **online processing of thermographic data** for controlling time-critical thermal processes. With the **industrial-grade light metal housing (IP67)** installations in manufacturing processes are easily possible even in harsh process environments. Even monitoring tasks requiring **automatic continuous operation** can be implemented easily.

Application areas:

- Real time thermography for industry and science
- Assembly control and process monitoring
- Machine and plant monitoring
- Security engineering
- Early fire detection

		(640×480)
Detector format (IR pixels)		
Lens	Focal length (mm)	FOV (°)
Wide-angle lens 60°	10	(57,1 × 44,4)
Standard lens 30°	20	(30,4 × 23,1)
Telephoto lens 15°	40	(15,5 × 11,6)

Additional infrared interchangeable lenses are available on request.



InfraTec GmbH Infrarotsensorik und Messtechnik Gostritzer Str. 61 – 63 01217 Dresden / GERMANY Phone +49 351 871-8630 Fax +49 351 871-8727 E-mail thermo@InfraTec.de



Studánková 395, 149 00 Praha 4 - Újezd tel.: +420 272 942 720, fax: +420 272 942 722 email: info@tmvss.cz, www.tmvss.cz

Further information at: www.InfraTec.eu